

Industrial Monitor

Style 736

Unique Features of Protek Industrial Monitors

- 1 One-piece seamless brass tube
- 2 Powder coating produces a tough, corrosion resistant finish
- 3 Stainless steel lever for durability and easy control
- 4 Double-row stainless steel ball bearings in monitor joints ensure smooth movements even when the monitor is under pressure
- 5 Positive friction locks for both horizontal and vertical travel to hold desired position
- 6 Extensive inlet options
- 7 Optimises advanced computer aided design and testing technology to minimise flow turbulence
- 8 Compatible with Protek's diverse range of water and self-educing foam monitor nozzles for various applications

Style 736 monitor shown with Style 823-BC nozzle



Industrial Monitor

Style 736

- Smooth internal waterway for efficient flow
- Seamless brass 2.5" waterway for flow rate of up to 1250 GPM (4800 LPM)
- Corrosion resistant brass construction ideal for marine, offshore, industrial and other corrosive environments
- Full 360° rotation
- Vertical travel of 135° from 90° above and 45° below horizontal
- Stainless steel balls in all swivels
- Positive friction locks for both horizontal and vertical travel to hold desired position
- Operating pressure of 200 psi (14 bar)
- Stainless steel lever for durability and easy control
- FM approved

Specification

		Style 736			
Max. GPM (LPM)		1250 (4800)			
Inlet	Size	3"	4"	6"	3"
	Type	Flange		Female Thread	
Outlet		2-1/2"			
Control		Tiller Bar			
Material		Brass			
Finish		Red Powder Coating			
Friction Loss		24 psi at 1250 GPM			
		20 psi at 1000 GPM			
Travel		135° Vertical			
		360° Rotation			
Weight		44 Lbs. (20 kg)			
Cercification		FM			

