

## Spinning Teeth Nozzles

Lightweight Anodized aluminium construction. Combination fog and straight stream with selectable gallonage. NH 1-1/2" / NH 2-1/2" female thread. Protective rubber bumper. Furnished with pistol grip and shut-off handle.

### Features

- Spinning teeth produces a wide range of droplet sizes and provides maximum heat absorption.
- Full time inlet swivel for quick attachment to fire-hose, ease of control on charged lines.
- Rubber pistol grip for better control and maneuverability.

Size : NH 1-1/2" / NH 2-1/2"  
 Flow Rate (MAX.) : 470LPM / 935LPM (7kg f/cm<sup>2</sup>)  
 Shooting Range : 40 m / 45 m (7kg f/cm<sup>2</sup>)  
 Material : Aluminium



SL-13DBS



SL-13BPS

Model	Size	Flow Rate(7kgf/cm <sup>2</sup> )	Length	Weight	Material & Remarks
SL-13DBS	NH 1-1/2"	150-225-360-470 LPM	250mm	2.0kg	Anodized Aluminium
SL-13BPS	NH 2-1/2"	470-660-755-935 LPM	320mm	3.0kg	

## High Fog Nozzle

Anodized aluminum construction. Fog, mist and straight stream combination. Three ball valve positions: Straight - Shut-off - Fog.



SL-69F

(Fog)



(Mist)



(Straight)



Model	Size	Flow Rate(7kgf/cm <sup>2</sup> )	Length	Weight	Material & Remarks
SL-69F	NH 1-1/2"	190 LPM	460mm	2.5kg	Anodized Aluminium

Available in NH 2-1/2"