

5ELEM[®]

UL Listed Hose



“5ELEM” Premium grade, single jacket multi-purpose fire hose, carefully designed and manufactured for fire brigade, transporting water both on land and on ships. This hose is rugged yet lightweight and can withstand deterioration and attack by most chemicals.

Jacket: The jackets are seamless and consist of filament synthetic polyester filler threads woven around the hose throughout its length and spun synthetic polyester warp threads interwoven with and substantially covering the filler thread. The jacket adjacent to the lining adheres firmly to the lining.

Lining: The lining of the hose consists of high quality black ethylene propylene rubber (EPDM) tube, compound EPDM1. The waterway surface is practically free from pitting, corrugations or other irregularities or imperfections. Withstand heat; resist ozone, weather, and aging, etc.

Length: 20, 30 meters

Features: Light in weight and flexible
Large flow
Weather-resistant
Easy care
Small roll diameter
Meet or exceeds NFPA 1961 and UL-19 specification (File EX6627)

Technical data (Hydrostatic tested to UL's standard):

Diameter Available	1.5" / 2.5"
Service Pressure	200 psi
Test Pressure	400 psi
Burst Pressure	600 psi

Technical improvements subject to alteration without prior notice.

Available couplings: (Optional)



Pin-lug expansion ring
(American standard)



German Storz



John Morris BS366
(British Instantaneous)



Nakajima

Imported and distributed by Champ Marketing Co.,Ltd. Tel.02-745-7891-4 Fax.02-398-3980