

Photoelectric Smoke Detector

| | |
|-----------------------|------------------------------|
| Model | : S-314 |
| Operating Sensitivity | : Comply to UL268, EN54, CNS |
| Operating Current | : 12 ~ 24 V DC Under 30 mA |
| Ambient Temperature | : -10 °C ~ + 55 °C |
| Monitoring Current | : Under 75 uA |
| Relative Humidity | : 10 ~ 95 % |
| Material | : Fire-proof plastic |
| Color | : White |

Effective Alert Area
Building Height : Under 4M / 4~20M
Area Covered : 150M² / 75M²



S-314

Rate-of-Rise Heat Detector



S-302

| | |
|---------------------|-----------------------|
| Model | : S-302 |
| Alarm Temperature | : Comply to EN54, CNS |
| Voltage Range | : 12 ~ 30V DC |
| Alarm Current | : 25 mA |
| Ambient Temperature | : 0 °C ~ + 55 °C |
| Material | : Fire-proof plastic |
| Color | : White |

Effective Alert Area
Construction / Height : Under 4M / 4M ~ 8M
Fire-proof Building : 90M² / 45M²
Ordinary Building : 50M² / 30M²

Fixed Temperature Detector



S-318

| | |
|---------------------|----------------------------|
| Model | : S-318 |
| Voltage Range | : 12 ~ 30V DC |
| Alarm Current | : 25 mA (Max) |
| Thermal Setting | : 70 °C or other selection |
| Ambient Temperature | : -10 °C ~ + 55 °C |
| Material | : Fire - proof plastic |
| Color | : White |

Effective Alert Area
Construction / Height : Under 4M / 4M ~ 8M
Fire-proof Building : 60M² / 30M²
Ordinary Building : 30M² / 15M²

Combination Heat Detector

| | |
|---------------------|----------------------------------|
| Model | : S-319 |
| Voltage Range | : 12 ~ 30V DC |
| Alarm Current | : 25 mA |
| Nominal Temperature | : Rate of Rise & Fix.Temp. 70 °C |
| Ambient Temperature | : 0 °C ~ + 55 °C |
| Material | : Fire-proof plastic |
| Color | : White |



S-319