

Photoelectric Smoke Detector

S-315



Characteristics

- Magnetic test feature makes maintenance easy and simple.
- Dual LEDs for 360 - degree visibility.
- The standard detector is 2 - wire or 3 - wire. For 4 - wire type just add one relay out - put module. Simple and easy module placement enables wider application and flexible stock control.
- Detector is made of high endurance, solid and colorfast Fire - proof plastic.
- Non - loosening screws on base terminal for easy installation.
- Detector has passed strict EMC test, which greatly eliminates false alarms caused by interference from nearby sources.

Specification

Model	S-315-2	S-315-3	S-315-4
Type	2-wire	3-wire	4-wire
Alarm Contact	N/A	N/A	0.8A @30V DC 0.4A @125V AC
Voltage Range		12~30V DC	
Alarm Current @24V DC 470	40mA	40mA	45mA
Standby Current		25 ~ 75 μ A	
Sensitivity Setting		Comply to EN54	
Ambient Temperature		-10C°~ +55C°	
Material		Fire-proof plastic	
Dimensions		102mm(Dia) x 47mm(H)	
Weight	130g	130 g	145g
Color		White	

Effective Alert Area

Building Height	Under 4M	4 ~ 20M
Area Covered	150 M ²	75 M ²