


300 PSI rated pressure



A55

ANGLE HOSE VALVE

DOUBLE FEMALE



SIZE (a x b)	CERTIFICATIONS	A	B	C	D	E
1 1/2" x 1 1/2"		4 1/32"	7 19/32"	2 5/32"	1 7/8"	3 11/16"
2 1/2" x 2 1/2"		5 1/8"	10 19/32"	3 5/32"	2 5/8"	5 11/32"

Used with a Fire Hose Rack Assembly, or as a Fire Dept. outlet connection.

Standard equipment:

Female NPT inlet and outlet forged brass valve.
Red handwheel.

RELATED PRODUCTS



A65 p. 28 **A70** p. 37 **A7B** p. 40


300 PSI rated pressure



A56

ANGLE HOSE VALVE

FEMALE x MALE hose connection



SIZE (a x b)	CERTIFICATIONS	A	B	C	D	E
1 1/2" x 1 1/2"		4 1/32"	7 19/32"	2 1/4"	1 7/8"	3 13/16"
2 1/2" x 2 1/2"		5 1/8"	10 19/32"	3 3/16"	2 5/8"	5 3/8"

Used with a Fire Hose Rack Assembly, or as a Fire Dept. outlet connection.

Standard equipment:

Female NPT inlet x male hose thread outlet forged brass valve.
Red handwheel.

RELATED PRODUCTS



A80 p. 35 **A70** p. 37 **A7B** p. 40