

Carbon Dioxide Self-Expelling Extinguisher Models

These quality fire extinguisher models are extremely versatile and ready to tackle flammable liquid and electrical fire hazards. They are ideally suited for indoor applications where delicate equipment or processes require a clean extinguishing agent.

Carbon Dioxide is an effective and clean gaseous extinguishing agent that does not leave any residue to clean up. These models are suitable for use on Class B and C fires.

**B5V****B10V**

*Economical, clean fire suppression agent
leaves no residue • no cleanup*

BADGER*Extra* Carbon Dioxide Features

- 5, 10, 15 and 20 pound models
- Heavy duty chrome plated brass valves
- Stainless steel handles, levers & hose bands
- Large loop stainless steel pull pins with tether
- Aluminum internal siphon tubes
- Extruded aluminum D.O.T. specification cylinders
- Easy to read color coded two piece nameplates
- Corrosion resistant epoxy powder paint finish
- UL Listed and USCG Approved – meets D.O.T. requirements
- 5 year periodic hydrostatic test interval
- 6 year product warranty
- Available with hanger hook or brackets

Technical Data: Badger Carbon Dioxide Self-Expelling Extinguisher Models

MODEL NUMBER	B5V	B10V	B15V	B20V
NOMINAL CAPACITY (LBS) (KILOGRAMS)	5 2.27	10 4.54	15 6.8	20 9.07
UL FIRE RATING	5B:C	10B:C	10B:C	10B:C
EXTINGUISHING AGENT TYPE	CO2	CO2	CO2	CO2
ITEM PART NUMBER	21111	21106	21103	21096
VALVE MATERIAL	PLATED BRASS	PLATED BRASS	PLATED BRASS	PLATED BRASS
CYLINDER MATERIAL	ALUMINUM	ALUMINUM	ALUMINUM	ALUMINUM
SHIPPING WEIGHT (LBS) (KILOGRAMS)	15 6.8	30 13.6	40 18.1	51 23.1
OPERATING PRESSURE	850 PSI @ 70°F	850 PSI @ 70°F	850 PSI @ 70°F	850 PSI @ 70°F
TEMPERATURE RANGE (F) (C)	-40° to 120° -40° to 49°	-40° to 120° -40° to 49°	-40° to 120° -40° to 49°	-40° to 120° -40° to 49°
DISCHARGE TIME (SECONDS)	9	10	14	17
DISCHARGE RANGE (FEET) (METERS)	3 to 8 0.9 to 2.4	3 to 8 0.9 to 2.4	3 to 8 0.9 to 2.4	3 to 8 0.9 to 2.4
UNIT HEIGHT (INCHES) (CENTIMETERS)	17 43.2	19.3 49.2	26 66	26 66
UNIT WIDTH (INCHES) (CENTIMETERS)	8.5 21.6	10.87 27.6	10.87 27.6	12 30.5
UNIT DEPTH (INCHES) (CENTIMETERS)	5.25 13.34	6.87 17.46	6.87 17.46	8 20.32
USCG APPROVAL	Type B:C Size -I	Type B:C Size -I	Type B:C Size -II	Type B:C Size -II
USCG BRACKET	VB-1 OPTIONAL	VB-2 OPTIONAL	VB-2 OPTIONAL	RB-4 OPTIONAL

This information is subject to change without notice. Badger Fire Protection disclaims any liability for any errors or misinterpretation of the information contained therein. Contact Badger Fire Protection for your local distributor for assistance.

Distributed by:



Badger Fire Protection

4251 Seminole Trail • Charlottesville, VA 22911

Tel 800 446 3857 or 434 973 4361

Fax 800 248 7809 or 434 973 1589

www.badgerfire.com