



CARBON DIOXIDE HAND-HELD AND WHEELED FIRE EXTINGUISHERS

FEATURES:

- Residue-free carbon dioxide gas extinguishing agent.
- Hand-held units use aluminum cylinders with a baked-on polyester enamel coating to withstand harsh environments.
- Wheeled units are constructed with spun steel cylinders, rugged frames, and pneumatic tires and are designed to be easily operated by one person.
- All units manufactured to ANSI/UL 154 and ANSI/UL 711 Standards and use DOT compliant cylinders.
- Plated brass valves on both hand-held and wheeled units.
- Optional tow loops offered on the wheeled extinguishers.

TYPICAL USES: Refineries, shipboard, laboratories, construction sites, chemical plants, and manufacturing facilities.



Hand-Held Extinguishers				
Model	5CD	10CD	15CD	20CD
Part Number	45100	45600	46100	46600
Agent Capacity	5 lbs. (2.27 kg)	10 lbs. (4.54 kg)	15 lbs. (6.80 kg)	20 lbs. (9.07 kg)
UL Rating	5B:C		10B:C	
Discharge Time	8 seconds	10 seconds	15 seconds	20 seconds
Range	4-8 ft (1.2-2.4 m)			
Bracket	Wall			
USCG Approval	Type B:C Size I		Type B:C Size II	
Ship Wt.	13.75 lbs. (6.3 kg)	27.75 lbs. (12.6 kg)	37.75 lbs. (17.1 kg)	49.0 lbs. (22.2 kg)
Height	17.375 in (44.1 cm)	19.75 in (50.2 cm)	26.375 in. (67 cm)	26.875 in (68.2 cm)
Width	8.25 in (21 cm)	12 in (30.5 cm)		13 in (33 cm)
Diameter	5.25 in (13.3 cm)	6.89 in (17.5 cm)		8 in (20.3 cm)

Wheeled Extinguishers								
Model	Part #	Capacity	UL Rating	Discharge Time	Range	Unit Height x Width x Depth	Hose Dia x Length	Ship Weight
C-50-SE	35050	50 lbs. (22.68 kg)	20B:C	40 seconds	15 ft (4.6m)	60 x 30 x 21 in (152.4 x 76.2 x 53.3 cm)	1 in x 15 ft (2.5 cm x 4.56 m)	250 lbs. (113.4 kg)
C-100-SE	35100	100 lbs. (45.36 kg)		80 seconds		65 x 30 x 21 in (165.1 x 76.2 x 53.3 cm)	1 in x 40 ft (2.5 cm x 12.2 m)	390 lbs. (176.9 kg)