



# 8011

## Photoelectric Smoke Detector

### Characteristics

- Magnetic test feature makes maintenance easy and simple.
- Dual LEDs for 360-degree visibility.
- The standard detector is 2-wire or 3-wire. For 4-wire type just add one relay output module on 3-wire base. Simple and easy module placement enables wider application and flexible stock control.
- Detector is made of high endurance, solid and colorfast Fire-proof plastic.
- Non-loosening screws on base terminal for easy installation.
- Detector has passed strict EMC test, which greatly eliminates false alarms caused by interference from nearby sources.

### Specifications


Model	8011-2	8011-3	8011-4
Alarm Contact	N/A	N/A	0.8A @30V DC 0.4A @125VAC
Voltage Range	12 ~ 30V DC		
Alarm Current @24V DC 470Ω	40mA	40mA	45mA
Standby Current @24V DC 470Ω	25 ~ 75μA		
Sensitivity Setting	Comply to EN54		
Ambient Temperature	-10°C ~ +55°C		
Material	Fire-proof plastic		
Dimensions	102mm(Dia.) x 47mm(H)		
Weight	130g	130g	145g
Color	White		

### Effective alert area

Building Height	Area Covered
Under 4M	150 M <sup>2</sup>
4 ~ 20M	75 M <sup>2</sup>

### Order information

8011-2	2-wire
8011-3	3-wire with remote indicator output
8011-4	4-wire with relay output
8011-2M	2-wire + magnetic test feature
8011-3M	3-wire with remote indicator output + magnetic test feature
8011-4M	4-wire with relay output + magnetic test feature



**HORING LIH INDUSTRIAL CO., LTD.**

4F., No. 18, Lane 327, Chung Shan Road, Sec. 2, Zhonghe District 235, New Taipei City, **Taiwan**

**Tel :** +886 2 22487599 **Fax :** +886 2 22407752 **Email :** export@horinglih.com **Website :** www.horinglih.com