

AH-8321

Photoelectric Smoke Detector



Characteristics

- Electronic Circuit are mainly use ONECHIP HIBRID IC and SMT technology, low profile design, low power consumption, high precision and stability.
- This item has passed EMC test with highest level requirement, so it will not easily be affected by electro-magnetic field, thunder strike and other interference source from the installation site.
- Regularly measures smoke particle level from smoke chamber, and with double-check feature to avoid false alarm.
- Every detector has used static process to eliminate dust inside the chamber before shipping. The special desing of smoke chamber could effectively prevent the access for external light and dust.
- Monitoring LED is also available on model (AH-0131).



Specifications

Model	AH-8321		
Type	2-wire	3-wire	4-wire
Alarm Contact	N/A	N/A	0.8A @30V DC 0.4A @125V AC
Voltage Range	12 ~ 30V DC		
Alarm Current @24V DC 470Ω	35mA	35mA	30mA
Permissible Current	185mA		
Standby Current	Under 30μA		
Sensitivity Setting	Comply to UL268, EN54, CNS		
Ambient Temperature	-10°C ~ +55°C		
Material	Fire-proof plastic		
Dimensions	102mm(Dia.) x 50mm(H)		
Weight	About 170 g		
Color	White		

Effective alert area

Building Height	Area Covered
Under 4M	150 M ²
4 ~ 20M	75 M ²

HORING LIH INDUSTRIAL CO., LTD.

4F., No. 18, Lane 327, Chung Shan Road, Sec. 2, Zhonghe District 235, New Taipei City, **Taiwan**

Tel : +886 2 22487599 Fax : +886 2 22407752 Email : export@horinglih.com Website : www.horinglih.com