
ADJUSTABLE FOG NOZZLES
A7A, A7B AND A7BP SERIES



A7A | A7B | A7BP

Description

A fog nozzle is a firefighting hose spray nozzle that breaks its stream into small droplets. Fog nozzles play an important part in firefighting tactics due to their versatility. By doing so, its stream achieves a greater surface area, and thus a greater rate of heat absorption, which, when compared to that of a smoothbore nozzle, speeds its transformation into the steam that smothers the fire by displacing its oxygen.

Versions and product codes

Series	Size	Type	Finishing
A7A	1 1/2"	Hose thread	Rough Brass Polished Brass Rough Chrome
A7B	1 1/2"	Hose thread	Rough Brass Rough Chrome
	2 1/2"		
A7BP	1 1/2"	Hose thread	Plastic

Technical data

• Rated pressure: 100 PSI (6,89 bar)

Materials: A7A

• Body: forged brass CuZn40Pb2 in accordance with European Standard EN 12165 CW617N, similar to American Standard ASTM B124 C37700
- Yield stress of the material in the shape of bar: 360 MPa
- Stress for permanent distortion R(0.2): 138 MPa
- Elongation: 10 %

Materials: A7B

• Body: forged brass CuZn40Pb2 in accordance with European Standard EN 12165 CW617N, similar to American Standard ASTM B124 C37700
- Yield stress of the material in the shape of bar: 360 MPa
- Stress for permanent distortion R(0.2): 138 MPa
- Elongation: 10 %

Materials: A7BP

• Body: polycarbonate

Approvals: A7A

1 1/2": FM APPROVED, UL LISTED 647X, ULC 647X

Approvals: A7B

1 1/2": FM APPROVED, UL LISTED 97X7, ULC 647X


2 1/2": UL LISTED 647X, ULC 647X

Approvals: A7BP

1 1/2": FM APPROVED, UL LISTED 647X, ULC 647X


Dimensions

A7A – ADJUSTABLE FOG NOZZLE




Size	A
1 1/2"	3 13/16"

A7B – ADJUSTABLE FOG NOZZLE WITH RUBBER BUMPER



Size	A
1 1/2"	3 13/16"
2 1/2"	5 9/16"

A7BP – PLASTIC ADJUSTABLE FOG NOZZLE WITH RUBBER BUMPER



Size	A
1 1/2"	4 37/64"

Product specifications

A7A 1 1/2"

Forged Brass Nozzle with adjustment from full fog to shut-off, with main feature as following:
- 1 1/2" hose thread
- Rated pressure 100 psi
- FM approved, UL & ULC listed

A7B 1 1/2"

Forged Brass Nozzle with adjustment from full fog to shut-off with rubber bumper, with main feature as following:
- 1 1/2" and 2 1/2" hose thread
- Rated pressure 100 psi
- FM approved, UL & ULC listed

A7B 2 1/2"

Forged Brass Nozzle with adjustment from full fog to shut-off with rubber bumper, with main feature as following:
- 1 1/2" and 2 1/2" hose thread
- Rated pressure 100 psi
- UL & ULC listed

A7BP 1 1/2"

Plastic Nozzle in ABS with adjustment from full fog to shut-off with rubber bumper, with main feature as following:
- 1 1/2" hose thread
- Rated pressure 100 psi
- FM approved, UL & ULC listed

Additional information
For additional information please check the website www.giacomini.com or contact the technical service: ☏ +39 0322 923372 🖷 +39 0322 923255 ✉ consulenza.prodotti@giacomini.com
This pamphlet is merely for information purposes. Giacomini S.p.A. retains the right to make modifications for technical or commercial reasons, without prior notice, to the items described in this pamphlet. The information described in this technical pamphlet does not exempt the user from following carefully the existing regulations and norms on good workmanship.
Giacomini S.p.A. Via per Alzo, 39 - 28017 San Maurizio d'Opaglio (NO) Italy

Model A7

File Number: EX3252

COMPANY

GIACOMINI SPA

VIA PER ALZO 39

S MAURIZIO D'OPAGLIO, NO 28017 Italy

MODEL INFO

A7

Basic spray nozzle

BASIC SPRAY NOZZLES

Fire Type	Size, in.	Max Inlet Pressure, psig (kPa)	Rated Operating Pressure, psig (kPa)	Rated Flow at Rated Operating Pressure, gpm (L/min)	Flow in Wide Open Position at 100 psig, gpm (L/min)	Inlet Thread Configurations
Class A and B	1-1/2	200 (1379)	100 (689)	110 (416)	110 (416)	NH, NPSH, NYFD
Class A and B	2-1/2	175 (1207)	100 (689)	273 (1033)	273 (1033)	NH, CSA

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."