



Copper Tube



Quality Products approved by TÜV, JIS and KITEMARK under the production operation of ISO 9001.

Copper Tube : ASTM B88

Outer Diameter		Type K		Type L		Type M	
inch	mm	Thickness (mm)	Weight (kg/pcs.)	Thickness (mm)	Weight (kg/pcs.)	Thickness (mm)	Weight (kg/pcs.)
3/8"	9.520	0.890	1.290	0.762	1.08	-	-
1/2"	12.700	1.240	2.387	0.889	1.71	0.635	1.287
5/8"	15.880	1.240	3.049	1.016	2.46	0.710	1.809
3/4"	19.050	1.240	3.710	1.066	3.12	0.762	2.341
7/8"	22.230	1.650	5.704	1.143	3.90	0.812	2.921
1-1/8"	28.570	1.650	7.462	1.270	5.63	0.889	4.134
1-3/8"	34.920	1.650	9.222	1.397	7.62	1.066	6.062
1-5/8"	41.270	1.828	12.112	1.524	9.81	1.244	8.365
2-1/8"	53.970	2.108	18.366	1.778	15.09	1.473	12.990
2-5/8"	66.670	2.413	26.048	2.032	21.31	1.651	18.034
3-1/8"	79.370	2.768	35.621	2.286	29.60	1.828	23.813
3-5/8"	92.075	3.048	45.587	2.540	38.20	2.108	31.861
4-1/8"	104.775	3.403	57.954	2.794	47.86	2.413	41.495
5-1/8"	130.175	4.060	85.900	3.175	67.75	2.770	59.200

Note : Copper Tube Type L Length 5.8 m.

