



Fire Alarm Bell



Modular Alarm Bells

Basic bell mounting plate to meet installation requirements.

Low Power Consumption

Enables using bell in sufficient quantity for uniform distribution

Installation Note


- Remove a gong.
- Wire the bell in the circuit.
- Mount bell mechanism on 4" square standard outlet box with the striker facing down.
- Remove a gong.
- The bell must be mounted a minimum of 8ft., above the floor, or, as close to the ceiling as possible.


11Z4

AIP-1024

AIP-624B

Polarized bell provides Red(+) and Black(-) lead wires. When you install the bell, must be observed the polarity.





Coil Driven	Type Ala	rm Bell				
Model	Gong Size	(Inch)	Rated Voltage	Rated Current	db@10ft	Approval
AIP-1024	6		24VDC	100mA	95	UL

Motor Driv	en Type Alarm E	Bell			
Model	Gong Size (Inch)	Rated Voltage	Rated Current	db@10ft	Approval
AIP-624B	6	24VDC	20mA	95	UL

Distributor: Champ Marketing Co.,Ltd. 3280-3282 Sukhumvit Road, Bangna, Bangkok 10260 Thailand Tel.02-7457891-4 Fax.02-3983980 http://www.ChampMarketing.com

Signaling

CE029