



A85

A86

Description

Casted bronze globe hose valve, straight pattern for the control of the flow of water from a pipe out to the valve and usually along a standpipe riser. Turning the handle of the hose valve allows the water to flow out from the valve, or shuts it off to prevent any more water from running out.

It is used with a Fire Hose Rack Assembly, or as a Fire Department outlet connection.

2 1/2" NPT inlet and 2 1/2" Female NPT outlet (A85) or 2 1/2" male hose thread outlet (A86). 175 lbs rated. With red handweel.

Versions and product codes

Series	Size	Type	Finishing
A85	2 1/2" x 2 1/2"	NPT inlet (F) x NPT outlet (F)	Rough bronze
A86	2 1/2" x 2 1/2"	NPT inlet (F) x Hose thread outlet (M)	Rough bronze

Technical data

- Rated pressure: 175 PSI (12 bar)

Materials

- Body: casted Bronze CB491K UNI EN1982-2000
- Tensile strength of the material in the shape of bar: min. 220 MPa
- Stress for permanent distortion R(0.2): min. 110 MPa
- Elongation: min. 6 %
- Shutter: forged brass CuZn40Pb2 in accordance with European Standard EN 12165 CW617N, similar to American Standard ASTM B124 C37700
- Stem: brass EN 12164 CW614N similar to American Standard ASTM B124 C37700
- Handwheel: red painted aluminium


Approvals: A85 and A86




Certified as pressure restricting valve with shut off feature

Dimensions

A85 - FEMALE NPT THREAD x FEMALE NPT THREAD



A86 - FEMALE NPT THREAD x MALE HOSE THREAD



Product specifications

A85

Straight Globe Hose Valve, used with fire hose rack assembling or as Fire Department outlet connection with main feature as following:

- Casted bronze body
- Forged brass shutter
- 2 1/2" female NPT inlet
- 2 1/2" female NPT outlet
- Aluminum red painted hand wheel
- Rated pressure 175 psi
- UL-ULC listed

A86

Straight Globe Hose Valve, used with fire hose rack assembling or as Fire Department outlet connection with main feature as following:

- Casted bronze body
- Forged brass shutter
- 2 1/2" female NPT inlet
- 2 1/2" male hose thread outlet
- Aluminum red painted hand wheel
- Rated pressure 175 psi
- UL-ULC listed