

PORTABLE FIRE FIGHTING PUMP P509RS

SUPER BALLCOCK VALVE OPTIONAL



A NEW TYPE VALVE OF ONE-TOUCH OPERATION.

THIS PROMOTES FURTHER IMPROVEMENT IN EASY AND EFFICIENCY OF OPERATION.



55PS

Performance Curve 14.0 Full Throttle Governor set Nozzle diameter (m/m) 13.0 21 φ 12.0 11.0 ressure (kg/cm2) 10.0 28 φ 9.0 30 φ 8.0 7.0 6.0 5.0 Suction head 0.6 1.4 0.8 1.2 1.6 1.8 2 0


Discharge Volume (m3/min.)

Material of Impeller & Casing is applied rust proof HIGH STRENGTH LIGHT ALLOY for extra long life.

Three way starting method for emergency use;
ELECTRIC CELL STARTER

RECOIL STARTER
ROPE STARTER.

For accurate starting and quick discharge, operation procedures are indicated by big figures and operation panel is illuminated by panel light for easy operation at night.



SPECIFICATIONS

P509R S/M

MODEL	RABBIT P509R S/M
Туре	Light weight Portable Fire Pump
Dimensions	L. 666mm x W. 637mm x H. 720mm
Dry weight	About 88kgs. (S)/78kgs. (M)

PUMP

PUIVIP	
Model Name	P509
Туре	High Pressure One Stage Turbine Pumo
Inlet dia.	nominal 90mm. (3.5in.) or 75mm. (3in.)
Outlet dia.	nominal 65mm. (2.5in.)
Water discharge Performance	
Rated Pressure .	7. Okg/cm2 with nozzle dia. 30. Omm
Rated Discharge Volume	Over 1.55m3/min.
High Pressure	10. Okg/cm2 with nozzle dia. 23. Omm
Discharge Volume at High Pressure	Over 1.1m3/min.
Rated Revolution	5, 100r. p. m. (Governor set)
Pump Chamber Seal	Mechanical Unit Seal
Vacuum Pump	4-blade eccentric rotary type with Strainer
Vacuum	Water suction 9meter (Over 640mm Hg)
Lubrication	Automatic lubrication (SAE #30. in winter #20)
Option	Two way discharge port

ENGINE

Model	EP58
Туре	Water cooled Horizontal 2-Cylinder Gasoline Engine
No. of Cyliner - Bore x Stroke	2 - 76 x 70 (mm)
Total Displacement	635 cc.
Maximum Output	55PS
Fuel consumption	290 g/PS.h or 15 liter/hour/high pressure
Fuel tank capacity	about 12 liter
Ignition	(CDI) Solid state ignition
Plug	NGK B7HS
Fuel type	Lubricant gasoline mixed (30 : 1)
Starting	(S) Cell starter type (Cell, Recoil, Rope) (M) Manual starter type (Recoil, Rope)
Speed control	Eccentric gravity
Light	Search light 12V 25W Panel Light 12V 8W
Battery	12V 30AH (S)

STANDARD ACCESSORIES



- 1. SEARCH LIGHT UNIT
- 2. BATTERY CHARGER
- 3. TOOK KIT WITH TOOL BOX
- 4. JOINT
- 5. FUEL MIXER
- 6. OIL CUP
- 7. BULB
- 8. SPARK PLUG
- 9. FUSE
- 10. INSTRUCTION MANUAL