


PORTABLE FIRE FIGHTING PUMP

P572S

SEPARATE OIL FILLING SYSTEM




Separate Oil Filling System eliminates the need for fuel mixing.

If the lubricant oil become empty then a warning indicator will alert and the engine will shut down automatically.



52kW(70PS)

Performance Curve



Discharge Volume (m3/min.)


Material of Impeller & Casing is applied rust proof HIGH STRENGTH LIGHT ALLOY for extra long life.

Automatic decompression system has been added to the engine, which reduces recoil force and has an automatic choke to ensure a simple and trouble free start every time. Two way starting systems, cell starter and recoil starter.

Super Ball Cock valve is applied as standard, with step-less throttle device, it delivers smoother, fine discharge stetting.

Newly designed One-touch removable outer cover helps your quick and easy inspection and maintenance.





SPECIFICATIONS

P572S

| MODEL | RABBIT P572S |
|------------|---------------------------------|
| Туре | Light Weight Portable Fire Pump |
| Dimensions | L. 657mm x W. 584mm x H. 720mm |
| Dry weight | About 88kgs. |

PUMP

| TOM | | |
|--------------------------------|---|--|
| Model Name | P572 | |
| Туре | High Pressure One stage turbine pump | |
| Inlet dia. | nominal 90mm.(3.5in.) or 75mm.(3in.) | |
| Outlet dia. | nominal 65mm.(2.5in.) | |
| WATER DISCHARGE PERFORMANCE | | |
| Rated Pressure | 7.0kg/cm2 with nozzle dia.32mm | |
| Rated Discharge Volume | Over 1.80m3/min. | |
| High Pressure | 1.0MPa(10.0kg/cm2) with nozzle dia.25.5mm | |
| High Pressure Discharge Volume | Over 1.30m3/min. | |
| Rated Revolution | 5,200r,p.m. (Governor set) | |
| Pump Chamber Seal | Mechanical Unit Seal | |
| Vacuum Pump | Oilless system, 4-blade eccentric rotary type with Strainer | |
| Vacuum | -0.085MPa (Water suction 9 meter) | |
| | | |

ENGINE

| EP572 |
|---|
| Water Cooled, Horizontal 2 Cylinder Gasoline Engine |
| 2 - 80 x 70 (mm) |
| 723 cc. |
| 52kW(70PS) |
| 17.5 liter/hour/highest pressure |
| about 12 liter |
| (CDI) Solid state ignition |
| NGK B7HS |
| Automatic seperate oil filling system(2-cycle engine oil) |
| about 1.2 liter |
| Cell starter type and Recoil starter |
| Eccentric gravity |
| Search light 12V 25W |
| Panel lamp 12V 3Wx2 |
| 30A19R(12V 30AH) |
| |

Remarks: All above specifications are subject to change without notice.