

BS EN3 Water & Foam Type Fire Extinguisher



Pressure Equipment Directive
Approved Fire Extinguishers




Machinery Equipment Directive
Approved Fire Extinguishers



ISO 9001
Certified



เครื่องดับเพลิงชนิดน้ำยาโฟมสะสมแรงดัน
ตัวถังทำด้วยแผ่นเหล็กขึ้นรูป ภายในตัวถังเคลือบด้วยพลาสติก
เพื่อยืดอายุการใช้งานได้ยาวนาน ภายนอกเคลือบด้วยสีแดง
ป้องกันการเกิดสนิม วาล์วบังคับการฉีดทำด้วยทองเหลืองชุบ
โครเมี่ยมด้ามหิ้วและคันบีบทำด้วยเหล็กเคลือบสี มีมาตรวัด
แรงอัดดันภายใน สายฉีดทนแรงดันสูง พร้อมหัวฉีดชนิดพิเศษ
มีช่องอากาศเข้าผสมเพื่อทำให้เกิดฟองอากาศขยายมากขึ้น
เหมาะสำหรับดับไฟประเภท A เกิดจากเชื้อเพลิงที่เป็น ไม้ ,
กระดาษ, ผ้า, ยาง และพลาสติก และไฟประเภท B เกิดจากเชื้อ
เพลิงเหลวไวไฟ เช่น น้ำมันเบนซิน , ดีเซล , ทินเนอร์ , ไขมัน
และ สี ได้รับการรับรองมาตรฐาน BS.EN 3 จากสถาบัน BSI
(BRITISH STANDARD INSTITUTE)



- British Standards Institution – BSI approval.
- Foam type is suitable for Class A & B.
- Water type is suitable for Class A.
- Protective plastic lining.
- Colour coded for instant recognition.
- High quality and good value.
- ISO 9001 Certified System by QAS Australia.

TECHNICAL SPECIFICATION

EXTINGUISHER TYPE	9L FOAM
	STORE PRESSURE TYPE (NITROGEN PROPELLANT)
MODEL NO.	FEX 103
FIRE RATING	21A 183B
OPERATING TEMPERATURE	0°C TO 60°C
OPERATING PRESSURE	12 BAR
TEST PRESSURE	25 BAR
HEIGHT	625 MM.
FULL WEIGHT	13.5 KG.
DISCHARGE TIME	65 SECS
RANG OF THROW (APPROX)	4-5 M.
CARTON SIZE MM.	200 X 200 X 646